

T & PLANT ROOM



PERSONNEL DOORS AND EMERGENCY EXITS

THERMAL AND FIRE RATED STEEL DOORS

SUITABLE FOR BOTH INTERNAL AND EXTERNAL USE

ADS Windows and Doors
T 01752 890 900

E info@adswindowsanddoors.co.uk

W adswindowsanddoors.co.uk

UNIQUE RANGE FEATURES

FIRST AID ROOM

8-10 week lead time Up to 3m high 1 year warranty Climador seamless steel doors are thermally-rated and fire-rated and available as single or double-leaf door-sets for internal or external use in commercial, industrial, residential or hospital applications. Glazed leafs are available as an option and door can be supplied with or without a threshold.

Climador features:

- Galvanized steel sheet door leaf with polyester or powder coating thickness 0.8 - 1.5mm
- Total leaf thickness 63mm
 Door frame made from steel powder coated sections thickness 2.0mm
- Stainless steel handle,

- Mortise lock
 Choice of RAL colours
- Two hinges as standard
- Fitted with door sill and drip cap (for external doors) as standard.




UNIQUE RANGE FEATURES 8-10 week lead time Up to 3m high


1 year warranty

DECLARED PERFORMANCE		
ESSENTIAL CHARACTERISTIC	TECHNICAL SPECIFICATION	PERFORMANCE
Water tightness	PN-EN 1027:2001	class 4B
Resistance to wind load P1, P2	PN-EN 12211:2001	class 4B
Resistance to wind load	P3 PN-EN 12211:2001	class C3
Thermal resistance single door	PN-EN ISO 10077-1:2007	1,4 [W/m2K]
Thermal resistance double door	PN-EN ISO 10077-1:2007	1,7 [W/m2K]
Air permeability	PN-EN 1026:2011	class 1
THERMAL INSULATION PROPERTIES		$U_{\rm D} = 1.4/({\rm m}^2.{\rm K})$

Fig. 1 Cross-section of fire-rated single door with corner frame Fig. 2 Frame options

BB





22

CE



Clima for

PERSONNEL DOORS AND EMERGENCY EXITS

THERMAL AND FIRE RATED STEEL DOORS

SUITABLE FOR BOTH INTERNAL AND EXTERNAL USE

ADS Windows and Doors

Unit 1, Stowford Business Park, Ivybridge, Devon, PL21 0BE,

T 01752 890 900

E info@adswindowsanddoors.co.uk

W adswindowsanddoors.co.uk